

**NAME**

**t1ascii** – convert PostScript Type 1 font from binary to ASCII

**SYNOPSIS**

**t1ascii** [**-l** *length*] [*input* [*output*]]

**DESCRIPTION**

**t1ascii** converts Adobe Type 1 font programs in PFB (binary) format to PFA (hexadecimal) format. If the file *output* is not specified output goes to the standard output. If the file *input* is not specified input comes from the standard input.

**OPTIONS**

**--line-length=***num*, **-l** *num*

Set the maximum length of encrypted lines in the output to *num*. (These are the lines consisting wholly of hexadecimal digits.) The default is 64.

**--warnings**, **-w**

Warn when the input font contains lines longer than 255 characters. Long lines don't strictly conform to Adobe's Document Structuring Conventions, and may cause problems with older software.

**SEE ALSO**

**t1binary**(1), **t1unmac**(1), **t1mac**(1), **t1asm**(1), **t1disasm**(1)

*Adobe Type 1 Font Format*

**AUTHORS**

Lee Hetherington (ilh@lcs.mit.edu)

Eddie Kohler (ekohler@gmail.com)

Ported to Microsoft C/C++ Compiler and MS-DOS operating system by Kai-Uwe Herbing (herbing@netmbx.netmbx.de).