

Section name references in L^AT_EX*

Sebastian Rahtz

2010/04/30

Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

README The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

ChangeLog This file records the version history (also available as text file).

Options This file provides a short option summary.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroT_EX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

hyperref.dtx This is the source code documentation for hyperref.

backref.dtx “Back referencing from bibliographical citations”

☞ **nameref.dtx** “Section name references in L^AT_EX” (this file)

Contents

1	Introduction	2
2	History	2
3	Implementation	2
3.1	<code>\label</code> stuff	2
3.2	Changes of section macros	4
3.2.1	Class beamer	7
3.2.2	Theorems	7
3.3	Referencing stuff	7
3.4	Usage and frontend	9
3.5	Package <code>ifthen</code> support	9
3.6	Compatibility with <code>varioref</code>	10
3.7	Support for listings	12

*This file has version number v2.40, last revised 2010/04/30.

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
 SPQR CERN July 1994;
 Last mod. Sept. 3th MG;
 Sept. 19th SPQR;
 April 11th 1995 SPQR (added section formatting hook);
 April 14th 1995 SPQR (compatibility with hyperref);
 June 22 1995 SPQR (removed typeout from Sectionformat);
 September 22 1997 added varioref hacks by Corey Minyard;
 September 28th changes by David Carlisle.
 More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of `\section`, `\caption`, ...). Then the behaviour switched to expanding, because this allows to remove unwanted macros (`\label`, ...). Despite this method is used in package `titleref` and class `memoir`, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package `getttitlestring` that uses the non-expanding method as default. It also allows me to use this package in package `zref-titleref`. See the package documentation of package `getttitlestring` how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{getttitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

3 Implementation

```
1 (*package)
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{getttitlestring}[2009/12/18]
4 \RequirePackage{ltxcmds}[2009/12/12]
```

We redefine `\label` so that it also writes the name of the current section to the `.aux` file; if the name ends in a dot, we zap it. To allow for the `hyperref` package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
5 \def\strip@period#1.\relax#2\@@@{#1}
```

3.1 `\label` stuff

Here is tested, whether package `showkeys` is loaded. But if option `final` is used, the macros of `showkeys` are not defined, so we have to check an additional test.

```

6 \newif\ifNR@showkeys
7 \NR@showkeysfalse
8 \@ifpackageloaded{showkeys}{%
9   \begingroup
10    \@ifundefined{SK@@label}{%
11      }{%
12        \global\NR@showkeystrue
13      }%
14    \endgroup
15 }{}

16 \def\label#1{%
17   \@bsphack
18   \begingroup
19     \@onelevel@sanitize\@currentlabelname
20     \edef\@currentlabelname{%
21       \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
22     }%
23     \protected@write\@auxout{}{%
24       \string\newlabel{#1}{%
25         {\@currentlabel}%
26         {\thepage}%
27         {\@currentlabelname}%
28         {\@currentHref}{}%
29       }%
30     }%
31   \endgroup
32   \@esphack
33 }%

34 \ifNR@showkeys
35   \def\label#1{%
36     \@bsphack
37     \SK@\SK@@label{#1}%
38     \begingroup
39       \@onelevel@sanitize\@currentlabelname
40       \edef\@currentlabelname{%
41         \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
42       }%
43       \protected@write\@auxout{}{%
44         \string\newlabel{#1}{%
45           {\@currentlabel}%
46           {\thepage}%
47           {\@currentlabelname}%
48           {\@currentHref}{}%
49         }%
50       }%
51     \endgroup
52     \@esphack
53   }%
54 \fi

55 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

```

56 \@ifundefined{slabel}{}{%
57   \def\slabel#1{%
58     \@bsphack
59     \if@filesw
60       {%

```

```

61     \@onelevel@sanitize\@currentlabelname
62     \edef\@currentlabelname{%
63         \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
64     }%
65     \let\thepage\relax
66     \def\protect{\noexpand\noexpand\noexpand}%
67     \edef\@tempa{%
68         \write\@auxout{%
69             \string\newlabel{#1}{%
70                 {\thesubequation}%
71                 {\thepage}%
72                 {\@currentlabelname}%
73                 {\@currentHref}{-}}%
74         }%
75     }%
76     }%
77     \expandafter
78     }%
79     \@tempa
80     \if@nobreak\ifvmode\nobreak\fi\fi
81     \fi
82     \@esphack
83 }%
84 }

```

Overload an AMS L^AT_EX command, which uses `\newlabel`. Sigh!

```

85 \def\@writetocindents@{%
86     \begingroup
87     \for\@tempa:=-1,0,1,2,3\do{%
88         \immediate\write\@auxout{%
89             \string\newlabel{tocindent\@tempa}{%
90                 \csname r@tocindent\@tempa\endcsname}{-}{-}}%
91         }%
92     }%
93 }%
94 \endgroup
95 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

```

96 \def\NR@getttitle#1{%
97     \GetTitleString{#1}%
98     \let\@currentlabelname\GetTitleStringResult
99 }

```

First the numbered sections. While we are about it, put in a useful section formatting macro.

```

100 \let\NR@sect\@sect
101 \newcounter{section@level}
102 \def\@sect#1#2#3#4#5#6[#7]#8{%
103     \setcounter{section@level}{#2}%
104     \NR@getttitle{#7}%
105     \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{\Sectionformat{#8}{#2}}%

```

```

106 }
and now the unnumbered ones
107 \let\NR@ssect\@ssect
108 \def\@ssect#1#2#3#4#5{%
109   \NR@getttitle{#5}%
110   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
111 }

Support for class memoir.
112 \ltx@ifundefined{ifheadnameref}{%
113 }{%
114   \ltx@ifundefined{M@ssect}{%
115   }{%
116     \let\NRorg@M@ssect\M@ssect
117     \def\M@ssect#1#2#3#4#5#6[#7][#8]{%
118       \ifheadnameref
119         \NR@getttitle{#8}%
120       \else
121         \NR@getttitle{#7}%
122       \fi
123       \NRorg@M@ssect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}][{#8}]%
124     }%
125   }%
126 }

Parts and chapters are treated differently. sigh. \@part and \@spart are
\long because of class memoir.
127 \let\NR@part\@part
128 \long\def\@part[#1]#2{%
129   \NR@getttitle{#1}%
130   \NR@part[{#1}]{#2}%
131 }
132 \let\NR@spart\@spart
133 \long\def\@spart#1{%
134   \NR@getttitle{#1}%
135   \NR@spart{#1}%
136 }
137 \let\NR@chapter\@chapter
138 \def\@chapter[#1]#2{%
139   \NR@getttitle{#1}%
140   \NR@chapter[{#1}]{#2}%
141 }
142 \ifclassloaded{memoir}{%
143   \ltx@ifundefined{ifheadnameref}{%
144   }{%
145     \def\@chapter[#1]#2{%
146       \ltx@ifundefined{ch@pt@c}{%
147         \NR@getttitle{#1}%
148       }{%
149         \ifx\ch@pt@c\ltx@empty
150           \NR@getttitle{#2}%
151         \else
152           \def\NR@temp{#1}%
153           \ifx\NR@temp\ltx@empty
154             \expandafter\NR@getttitle\expandafter{\ch@pt@c}%
155           \else
156             \ifheadnameref

```

```

157         \NR@getttitle{#1}%
158     \else
159         \expandafter\NR@getttitle\expandafter{\ch@pt@c}%
160     \fi
161 \fi
162 \fi
163 }%
164 \NR@chapter[#{#1}]{#2}%
165 }%
166 }%
167 }{}
168 \let\NR@schapter\@schapter
169 \def\@schapter#1{%
170     \NR@getttitle{#1}%
171     \NR@schapter{#1}%
172 }

```

Captions

```

173 \AtBeginDocument{%
174     \@ifpackageloaded{hyperref}{%
175         \@ifpackagelater{hyperref}{2009/12/05}\@gobble\@firstofone
176     }\@firstofone
177     {%
178         \let\NR@@caption\@caption
179         \long\def\@caption#1[#2]{%
180             \NR@getttitle{#2}%
181             \NR@@caption{#1}[{#2}]%
182         }%
183     }%
184 \@ifpackageloaded{longtable}{%
185     \let\NRorg@LT@c@ption\LT@c@ption
186     \def\LT@c@ption#1[#2]#3{%
187         \NRorg@LT@c@ption{#1}[{#2}]{#3}%
188         \def\@tempa{#2}%
189         \ifx\@tempa\@empty
190             \else
191                 \NR@getttitle{#2}%
192             \fi
193         }%
194     }{}%

```

Environment 'description'.

```

195 \ltx@ifundefined{descriptionlabel}{%
196 }{%
197     \let\NRorg@descriptionlabel\descriptionlabel
198     \def\descriptionlabel#1{%
199         \NR@getttitle{#1}%
200         \NRorg@descriptionlabel{#1}%
201     }%
202 }%
203 }

```

Compatibility for package titlesec.

```

204 \AtBeginDocument{%
205     \@ifpackageloaded{titlesec}{%
206         \let\NRorg@ttl@sect@i\ttl@sect@i
207         \def\ttl@sect@i#1#2[#3]#4{%
208             \NR@getttitle{#4}%

```

```

209     \NRorg@ttl@sect@i{#1}{#2} [{#3}] {#4}%
210   }%
211 }{}%
212 }

```

3.2.1 Class beamer

```

213 \@ifclassloaded{beamer}{%
214   \def\NR@PatchBeamer#1{%
215     \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
216       \csname beamer@#1\endcsname
217     \begingroup
218       \edef\x{\endgroup
219         \long\def\expandafter\noexpand\csname beamer@#1\endcsname
220           [####1]{% hash-ok
221             \noexpand\NR@getttitle{####1}%
222             \expandafter\noexpand\csname NRorg@beamer@#1\endcsname
223               [####1]}%
224           }%
225         }%
226       \x
227     }%
228     \NR@PatchBeamer{section}%
229     \NR@PatchBeamer{subsection}%
230     \NR@PatchBeamer{subsubsection}%
231 }{}

```

3.2.2 Theorems

```

232 \ltx@ifundefined{@opargbegintheorem}{}{%
233   \let\NRorg@opargbegintheorem\@opargbegintheorem
234   \def\@opargbegintheorem#1#2#3{%
235     \NR@getttitle{#3}%
236     \NRorg@opargbegintheorem{#1}{#2}{#3}%
237   }%
238 }
239 \AtBeginDocument{%
240   \@ifpackageloaded{amsthm}{%
241     \let\NRorg@begintheorem\@begintheorem
242     \begingroup
243       \edef\x{macro:\string#1\string#2[\string#3]}%
244       \@onelevel@sanitize\x
245       \def\y#1->#2\@nil{#1}%
246       \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
247       \@onelevel@sanitize\z
248     \expandafter\endgroup
249     \ifx\x\z
250       \def\@begintheorem#1#2[#3]{%
251         \NR@getttitle{#3}%
252         \NRorg@begintheorem{#1}{#2} [{#3}]%
253       }%
254     \fi
255   }{}%
256 }

```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```

257 \providecommand*{\@currentlabelname}{}

```

```
258 \providecommand*\@currentHref}{}
```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```
259 \long\def\@firstoffive#1#2#3#4#5{#1}
260 \long\def\@secondoffive#1#2#3#4#5{#2}
261 \long\def\@thirdoffive#1#2#3#4#5{#3}
262 \long\def\@fourthoffive#1#2#3#4#5{#4}
263 \long\def\@fifthoffive#1#2#3#4#5{#5}
```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.

```
264 \providecommand*\@safe@activestruetrue{}%
265 \providecommand*\@safe@activesfalse{}%
266 \def\NR@setref#1{%
267   \begingroup
268     \@safe@activestruetrue
269     \expandafter
270     \endgroup
271   \expandafter\NR@@setref\csname r@#1\endcsname
272 }
273 \def\NR@@setref#1{%
274   \ifx\@undefined#1%
275     \let#1\relax
276   \fi
277   \@setref#1%
278 }
279 \def\T@ref#1{%
280   \NR@setref{#1}\@firstoffive{#1}%
281 }%
282 \def\T@pageref#1{%
283   \NR@setref{#1}\@secondoffive{#1}%
284 }%
285 \ifNR@showkeys
286   \ifx\SK@ref\@empty
287   \else
288     \def\T@ref#1{%
289       \@safe@activestruetrue
290       \SK@\SK@@ref{#1}%
291       \@safe@activesfalse
292       \NR@setref{#1}\@firstoffive{#1}%
293     }%
294     \def\T@pageref#1{%
295       \@safe@activestruetrue
296       \SK@\SK@@ref{#1}%
297       \@safe@activesfalse
298       \NR@setref{#1}\@secondoffive{#1}%
299     }%
300   \fi
301 \fi
```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`. Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```
302 \ifpackageloaded{hyperref}{%
```



```

303 }{%
304 \DeclareRobustCommand{\ref}{\T@ref}%
305 \DeclareRobustCommand{\pageref}{\T@pageref}%
306 }

```

3.4 Usage and frontend

Access the (third) name part with `\nameref`;

```

307 \def\T@nameref#1{%
308 \begingroup
309 \let\label@gobble
310 \NR@setref{#1}\@thirdoffive{#1}%
311 \endgroup
312 }%
313 \ifNR@showkeys
314 \ifx\SK@ref\@empty
315 \else
316 \def\T@nameref#1{%
317 \@safe@activestruer
318 \SK@\SK@@ref{#1}%
319 \@safe@activesfalse
320 \begingroup
321 \let\label@gobble
322 \NR@setref{#1}\@thirdoffive{#1}%
323 \endgroup
324 }%
325 \fi
326 \fi
327 %\@ifclassloaded{memoir}{%
328 % \ltx@ifundefined{mem@titlerefno link}\ltx@secondoftwo{%
329 % \ltx@ifundefined{mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
330 % }%
331 %}\ltx@secondoftwo
332 %{%
333 % \DeclareRobustCommand*{\nameref}{%
334 % \@ifstar\mem@titlerefno link\mem@titleref
335 % }%
336 %}{%
337 \DeclareRobustCommand*{\nameref}{%
338 \@ifstar\T@nameref\T@nameref
339 }%
340 %}

```

An extended form which gives title and page number.

```

341 \def\Name ref#1{'\nameref{#1}' on page~\pageref{#1}}

```

The default for `\Sectionformat`

```

342 \providecommand\Sectionformat [2]{#1}

```

3.5 Package ifthen support

Package `ifthen`'s `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```

343 \@ifpackageloaded{ifthen}{%

```

```

344 \let\NR@Org@ifthenelse\ifthenelse
345 \def\ifthenelse{%
346 \let\begin@group\NR@TE@begin@group
347 \NR@Org@ifthenelse
348 }%
349 \let\NR@Org@begin@group\begin@group
350 \def\NR@TE@begin@group{%
351 \let\begin@group\NR@Org@begin@group
352 \begin@group
353 \def\ref##1{\getrefbykeydefault{##1}{-}{??}}%
354 \def\pageref##1{\getrefbykeydefault{##1}{page}{0}}%
355 }%
356 }{}

```

3.6 Compatibility with varioref

[This section was derived by Corey Minyard minyard@acm.org from the varioref package]

```

357 \AtBeginDocument{%
358 \ifx\csname @v@pageref\endcsname\relax
359 \else
360 \def\@v@pageref#1[#2]#3{%
361 \begin@group
362 \csname @safe@activetrue\endcsname
363 \edef\x{#3}%
364 \@onelevel@sanitize\x
365 \toks@{%
366 \NR@@v@pageref{#1}[{#2}]}%
367 }%
368 \edef\x{\endgroup
369 \the\toks@{x}}%
370 }%
371 \x
372 }%
373 \def\NR@@v@pageref#1[#2]#3{%
374 \leavevmode\unskip
375 \global\advance\c@vrcnt\@ne
376 \@ifundefined{r@the\c@vrcnt @vr}{%
377 {\@namedef{r@the\c@vrcnt @vr}{??}{?}{-}{-}}}%
378 \edef\@tempa{%
379 \expandafter\expandafter\expandafter
380 \@secondoffive\csname r@the\c@vrcnt @vr\endcsname
381 }%
382 \@ifundefined{r@the\c@vrcnt @xvr}{%
383 {\@namedef{r@the\c@vrcnt @xvr}{??}{?}{-}{-}}}%
384 \edef\@tempb{%
385 \expandafter\expandafter\expandafter
386 \@secondoffive\csname r@the\c@vrcnt @xvr\endcsname
387 }%
388 {}%
389 \let\@currentlabel\@empty
390 \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
391 }%
392 \ifx\@tempa\@tempb
393 \else
394 \vref@err{%
395 \noexpand\vref at page boundary %

```

```

396     \@tempb-\@tempa\space (may loop)%
397   }%
398 \fi
399 \@ifundefined{r@#3}{\@namedef{r@#3}{??}{??}{-}{-}{-}}{}%
400 \edef\thepagerefnum{%
401   \expandafter\expandafter\expandafter
402   \@secondoffive\csname r@#3\endcsname
403 }%
404 \ifx\vref@space\@undefined
405   \space
406 \else
407   \vref@space
408 \fi
409 \ifx\@tempa\thepagerefnum
410   #1%
411 \else
412   #2%
413   \is@pos@number\thepagerefnum{%
414     \is@pos@number\@tempa{%
415       \@tempcnta\@tempa
416       \advance\@tempcnta\@ne
417     }{%
418       \@tempcnta\maxdimen
419     }%
420     \ifnum \thepagerefnum =\@tempcnta
421       \ifodd\@tempcnta
422         \if@twoside
423           \reftextfaceafter
424         \else
425           \reftextafter
426         \fi
427       \else
428         \reftextafter
429       \fi
430     \else
431       \advance\@tempcnta-2 %
432       \ifnum \thepagerefnum =\@tempcnta
433         \ifodd\@tempcnta
434           \reftextbefore
435         \else
436           \if@twoside
437             \reftextfacebefore
438           \else
439             \reftextbefore
440           \fi
441         \fi
442       \else
443         \reftextfaraway{#3}%
444       \fi
445     \fi
446   }{%
447     \reftextfaraway{#3}%
448   }%
449 \fi
450 {%
451   \let\@currentlabel\@empty
452   \expandafter\label\expandafter{\the\c@vrcnt @vr}%

```

```

453     }%
454   }%
455   \DeclareRobustCommand\vnameref[1]{%
456     \unskip~\nameref{#1}%
457     \@vpageref[\unskip]{#1}%
458   }%
459   \fi
460 }

461 \@ifundefined{@Refstar}{%
462   \def\T@Ref#1{%
463     \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
464   }%
465   \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
466     \MakeUppercase#1%
467   }%
468 }{}%
469 \AtBeginDocument{%
470   \@ifpackageloaded{varioref}{%
471     \@ifundefined{@Refstar}{%
472       \DeclareRobustCommand*\Ref}[1]{%
473         \T@Ref{#1}%
474       }%
475     }{}%
476   }{}%
477 }%

```

3.7 Support for listings

```

478 \AtBeginDocument{%
479   \@ifpackageloaded{listings}{%
480     \let\NR@Org@lst@MakeCaption\lst@MakeCaption
481     \def\lst@MakeCaption{%
482       \ifx\lst@label\@empty
483       \else
484         \let\@currentlabelname\lst@@caption
485       \fi
486       \NR@Org@lst@MakeCaption
487     }%
488   }{}%
489 }
490 </package>

```

4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

	Symbols	\@caption	178, 179	19, 20,
\@@@	5, 21, 41, 63	\@chapter .	137, 138, 145	21, 27, 39, 40,
\@@vpageref	360	\@currentHref	41, 47, 61, 62,
\@auxout	23, 43, 68, 88	28, 48, 73, 258	63, 72, 98, 257, 484
\@begintheorem	241, 246, 250	\@currentlabel	\@empty
\@bsphack	17, 36, 58	25, 45, 389, 451	189, 286,
			\@currentlabelname .		314, 389, 451, 482
				\@esphack	32, 52, 82

<code>\@fifthoffive</code>	263		
<code>\@firstoffive</code>	259, 280, 292		
<code>\@firstofone</code>	175, 176		
<code>\@fourthoffive</code>	262		
<code>\@gobble</code>	175, 309, 321		
<code>\@ifclassloaded</code>	142, 213, 327		
<code>\@ifpackagelater</code>	175		
<code>\@ifpackageloaded</code>	8, 174, 184, 205, 240, 302, 343, 470, 479		
<code>\@ifstar</code>	334, 338		
<code>\@ifundefined</code>	10, 56, 376, 382, 399, 461, 471		
<code>\@mem@titleref</code>	334		
<code>\@mem@titlerefnoLink</code>	334		
<code>\@namedef</code>	377, 383, 399		
<code>\@one</code>	375, 416		
<code>\@nil</code>	245, 246		
<code>\@onelevel@sanitize</code>	19, 39, 61, 244, 247, 364		
<code>\@opargbegintheorem</code>	233, 234		
<code>\@part</code>	127, 128		
<code>\@safe@activesfalse</code>	265, 291, 297, 319		
<code>\@safe@activestrue</code>	264, 268, 289, 295, 317		
<code>\@schapter</code>	168, 169		
<code>\@secondoffive</code>	260, 283, 298, 380, 386, 402		
<code>\@sect</code>	100, 102		
<code>\@setref</code>	277		
<code>\@spart</code>	132, 133		
<code>\@ssect</code>	107, 108		
<code>\@tempa</code>	67, 79, 87, 89, 90, 188, 189, 378, 392, 396, 409, 414, 415		
<code>\@tempb</code>	384, 392, 396		
<code>\@tempcnta</code>	415, 416, 418, 420, 421, 431, 432, 433		
<code>\@thirdoffive</code>	261, 310, 322		
<code>\@undefined</code>	274, 404		
<code>\@vpageref</code>	457		
<code>\@writetocindent</code>	85		
		A	
<code>\advance</code>	375, 416, 431		
<code>\AtBeginDocument</code>	173, 204, 239, 357, 469, 478		
		B	
<code>\begingroup</code>	9, 18, 38, 86, 217, 242, 267, 308, 320, 346, 349, 351, 352, 361		
		C	
<code>\c@vrcnt</code>	375, 376, 377, 380, 382, 383, 386, 390, 452		
<code>\ch@pt@c</code>	149, 154, 159		
<code>\csname</code>	90, 215, 216, 219, 222, 271, 358, 362, 380, 386, 402		
		D	
<code>\DeclareRobustCommand</code>	304, 305, 333, 337, 455, 472		
<code>\def</code>	5, 16, 35, 57, 66, 85, 96, 102, 108, 117, 128, 133, 138, 145, 152, 169, 179, 186, 188, 198, 207, 214, 219, 234, 245, 250, 259, 260, 261, 262, 263, 266, 273, 279, 282, 288, 294, 307, 316, 341, 345, 350, 353, 354, 360, 373, 462, 465, 481		
<code>\descriptionlabel</code>	197, 198		
<code>\do</code>	87		
		E	
<code>\edef</code>	20, 40, 62, 67, 218, 243, 246, 363, 368, 378, 384, 400		
<code>\else</code>	120, 151, 155, 158, 190, 287, 315, 359, 393, 406, 411, 424, 427, 430, 435, 438, 442, 483		
<code>\endcsname</code>	90, 215, 216, 219, 222, 271, 358, 362, 380, 386, 402		
<code>\endgroup</code>	14, 31, 51, 94, 218, 248, 270, 311, 323, 368		
<code>\expandafter</code>	21, 41, 63, 77, 154, 159, 215, 219, 222, 246, 248, 269, 271, 379, 385, 390, 401, 452		
		F	
<code>\fi</code>	54, 80, 81, 122, 160, 161, 162, 192, 254, 276, 300, 301, 325, 326, 398, 408, 426, 429, 440, 441, 444, 445, 449, 459, 485		
		G	
<code>\getrefbykeydefault</code>	353, 354		
<code>\GetTitleString</code>	97		
<code>\GetTitleStringResult</code>	98		
<code>\global</code>	12, 375		
		I	
<code>\if@filesw</code>	59		
<code>\if@nobreak</code>	80		
<code>\if@twoside</code>	422, 436		
<code>\ifheadnameref</code>	118, 156		
<code>\ifNR@showkeys</code>	6, 34, 285, 313		
<code>\ifnum</code>	420, 432		
<code>\ifodd</code>	421, 433		
<code>\ifthenelse</code>	344, 345		
<code>\ifvmode</code>	80		
<code>\ifx</code>	149, 153, 189, 249, 274, 286, 314, 358, 392, 404, 409, 482		
<code>\immediate</code>	88		
<code>\is@pos@number</code>	413, 414		
		L	
<code>\label</code>	16, 35, 55, 309, 321, 390, 452		
<code>\leavevmode</code>	374		
<code>\let</code>	55, 65, 98, 100, 107, 116, 127, 132, 137, 168, 178, 185,		

	197, 206, 215, 233, 241, 275, 309, 321, 344, 346, 349, 351, 389, 451, 480, 484	\NR@part 127, 130	
\long	128, 133, 179, 219, 259, 260, 261, 262, 263	\NR@PatchBeamer 214, 228, 229, 230	S
\lst@caption	484	\NR@schapter . . . 168, 171	\Sectionformat 105, 110, 342
\lst@label	482	\NR@sect 100, 105	\setcounter 103
\lst@MakeCaption	480, 481	\NR@setref . . . 266, 280, 283, 292, 298, 310, 322, 463	\SK@ . . . 37, 290, 296, 318 \SK@@label 37 \SK@ref . . . 290, 296, 318 \SK@ref 286, 314
\LT@c@ption . . . 185, 186		\NR@showkeysfalse . . 7	\slabel 57
\ltx@empty . . . 149, 153		\NR@showkeystrue . . 12	\space 396, 405
\ltx@firstoftwo . . . 329		\NR@spart 132, 135	\string 24, 44, 69, 89, 243
\ltx@ifundefined 112, 114, 143, 146, 195, 232, 328, 329		\NR@ssect 107, 110	\strip@period 5, 21, 41, 63
\ltx@label 55		\NR@TE@begingroup 346, 350	T
\ltx@secondoftwo 328, 329, 331		\NR@temp 152, 153	\T@nameref 307, 316, 338
M		\NR@Org@begingroup 349, 351	\T@pageref 282, 294, 305
\M@sect 116, 117		\NR@Org@begintheorem 241, 252	\T@Ref 462, 473
\MakeUppercase 466		\NR@Org@descriptionlabel 197, 200	\T@ref 279, 288, 304
\maxdimen 418		\NR@Org@ifthenelse 344, 347	\the 369, 376, 377, 380, 382, 383, 386, 390, 452
\meaning 246		\NR@Org@l@st@MakeCaption 480, 486	\the page . . . 26, 46, 65, 71
N		\NR@Org@LT@c@ption 185, 187	\thesubequation . . . 70
\NameRef 341		\NR@Org@M@sect . . 116, 123	\thevpage@refnum 400, 409, 413, 420, 432
\nameref 333, 337, 341, 456		\NR@Org@opargbegintheorem 233, 236	\toks@ 365, 369
\newcounter 101		\NR@Org@ttl@sect@i 206, 209	\ttl@sect@i 206, 207
\newif 6		P	U
\NewLabel 24, 44, 69, 89		\pageref . . . 305, 341, 354	\unskip 374, 456, 457
\nobreak 80		\protect 66	V
\noexpand 66, 219, 221, 222, 395		\protected@write 23, 43	\vnameref 455
\NR@@caption . . . 178, 181		\providecommand 257, 258, 264, 265, 342	\vref 395
\NR@@setref . . . 271, 273		R	\vref@err 394
\NR@@vpageref . . 366, 373		\Ref 472	\vref@space . . . 404, 407
\NR@chapter 137, 140, 164		\ref 304, 353	W
\NR@getttitle 96, 104, 109, 119, 121, 129, 134, 139, 147, 150, 154, 157, 159, 170, 180, 191, 199, 208, 221, 235, 251		\ref@textafter . 425, 428	\write 68, 88
\NR@MakeUppercaseFirstOfFive 463, 465		\ref@textbefore 434, 439	X
		\ref@textfaceafter . 423	\x 218, 226, 243, 244, 249, 363, 364, 368, 369, 371
		\ref@textfacebefore . 437	Y
		\ref@textfaraway 443, 447	\y 245, 246
		\relax 5, 21,	Z
		\RequirePackage . . 2, 3, 4	\z 246, 247, 249