

The l3keys2e package

L^AT_EX 2_ε option processing using L^AT_EX3 keys*

The L^AT_EX3 Project[†]

Released 2011/09/15

The key–value method for optional arguments is very popular, as it allows the class or package author to define a large number of options with a simple interface. The `expl3` bundle of L^AT_EX3 base code includes the module `l3keys` for defining keys, but to use these when loading L^AT_EX 2_ε packages and classes requires extra support. That support is provided by this small package, which is intended to enable L^AT_EX 2_ε packages to benefit from the power of the L^AT_EX3 key–value system.

0.1 Creating and using keyval options

As with any key–value input, using key–value pairs as package or class options has two parts. The first stage is to define one or more keys, using the `\keys_define:nn` function. For example, an option which simply stores a value would be created using:

```
\keys_define:nn { module }  
  { option .set:N = \l_module_variable_tl }
```

On its own, this will not make the key an option for the package or class containing the definition. The second stage is therefore to process the current options, searching for applicable keys.

`\ProcessKeysOptions` `\ProcessKeysOptions {<module>}`

The `\ProcessKeysOptions` function is used to check the current option list against the keys defined for `{<module>}`. Global (class) options and local (package) options are checked when this function is called in a package. Each option which does match a key name is then used to attempt to set the appropriate key using `\keys_set:nn`. For example, the option defined earlier would be processed by the line

```
\ProcessKeysOptions { module }
```

*This file describes v2828, last revised 2011/09/15.

[†]E-mail: latex-team@latex-project.org

`\ProcessKeysPackageOptions`

`\ProcessKeysPackageOptions {(module)}`

This function works in a similar manner to `\ProcessKeysOptions`. When used in a L^AT_EX 2_ε package, `\ProcessKeysPackageOptions` will not examine any class options available. In contrast, `\ProcessKeysOptions` does parse class options (in common with the L^AT_EX 2_ε kernel function `\ProcessOptions`).

0.2 l3keys2e Implementation

```
1 <*package>
2 \ProvidesExplPackage
3   {\ExplFileName}{\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
4
5   A check to make sure that expl3 is not too old
6   \ifpackagelater { expl3 } { 2011/09/15 }
7   { }
8   {
9     \PackageError { l3keys2e } { Support-package-l3kernel-too-old. }
10    {
11      Please~install~an~up~to~date~version~of~l3kernel~
12      using~your~TeX~package~manager~or~from~CTAN.\ \ \
13      Loading~l3keys2e~will~abort!
14    }
15  }
16  \tex_endinput:D
17 }
```

`\keys_latex_options_clist`

A single list is used for all options, into which they are collected before processing.

```
15 \clist_new:N \keys_latex_options_clist
    (End definition for \keys_latex_options_clist. This function is documented on page ??.)
```

`_l_keys_process_class_bool`

A flag to indicate that class options should be processed for packages.

```
16 \bool_new:N \_l_keys_process_class_bool
    (End definition for \_l_keys_process_class_bool. This function is documented on page ??.)
```

`\keys_latex_options:n`

The main function calls functions to collect up the global and local options into `\keys_latex_options_clist` before calling the underlying functions to actually do the processing. So that a suitable message is produced if the option is unknown, the special `unknown` key is set if it does not already exist for the current module.

```
17 \cs_new_protected:Npn \keys_latex_options:n #1
18   {
19     \clist_clear:N \keys_latex_options_clist
20     \keys_latex_options_global:n {#1}
21     \keys_latex_options_local:
22     \keys_if_exist:nnF {#1} { unknown }
23     {
24       \keys_define:nn {#1}
25       {
26         unknown .code:n =
27         {
```

```

28         \msg_error:nxxx { keyvalue } { option-unknown }
29         { \l_keys_key_tl } { \@currname }
30     }
31 }
32 }
33 \keys_set:nV {#1} \keys_latex_options_clist
34 \AtEndOfPackage { \cs_set_eq:NN \@unprocessedoptions \scan_stop: }
35 }

```

(End definition for \keys_latex_options:n. This function is documented on page ??.)

\keys_latex_options_global:n Global (class) options are handled differently for L^AT_EX_{2 ϵ} packages and classes. Hence this function is essentially a check on the current file type. The initial test is needed as L^AT_EX_{2 ϵ} allows variables to be equal to \scan_stop:, which is forbidden in L^AT_EX₃ code.

```

36 \cs_new_protected:Npn \keys_latex_options_global:n #1
37 {
38     \cs_if_eq:NNF \@classoptionslist \scan_stop:
39     {
40         \cs_if_eq:NNTF \@currentt \@clsextension
41         { \keys_latex_options_class:n {#1} }
42         {
43             \bool_if:NT \l_keys_process_class_bool
44             { \keys_latex_options_package:n {#1} }
45         }
46     }
47 }

```

(End definition for \keys_latex_options_global:n. This function is documented on page ??.)

\keys_latex_options_class:n For classes, each option (stripped of any content after =) is checked for existence as a key. If found, the option is added to the combined list for processing. On the other hand, unused options are stored up in \@unusedoptionlist. Before any of that, though, there is a simple check to see if there is an unknown key. If there is, then *everything* will match and the mapping can be skipped.

```

48 \cs_new_protected:Npn \keys_latex_options_class:n #1
49 {
50     \keys_if_exist:nnTF {#1} { unknown }
51     { \clist_put_right:No \keys_latex_options_clist \@classoptionslist }
52     {
53         \clist_map_inline:Nn \@classoptionslist
54         {
55             \keys_if_exist:nnTF {#1} { \keys_latex_remove_equals:n {##1} }
56             { \clist_put_right:Nn \keys_latex_options_clist {##1} }
57             { \clist_put_right:Nn \@unusedoptionlist {##1} }
58         }
59     }
60 }

```

(End definition for \keys_latex_options_class:n. This function is documented on page ??.)

`\keys_latex_options_package:n` For global options when processing a package, the tasks are slightly different from those for a class. The check is the same, but here there is nothing to do if the option is not applicable. Each valid option also needs to be removed from `\@unusedoptionlist`.

```

61 \cs_new_protected:Npn \keys_latex_options_package:n #1
62   {
63     \clist_map_inline:Nn \@classoptionslist
64       {
65         \keys_if_exist:nnT {#1} { \keys_latex_remove_equals:n {##1} }
66         {
67           \clist_put_right:Nn \keys_latex_options_clist {##1}
68           \clist_remove_all:Nn \@unusedoptionlist {##1}
69         }
70       }
71   }

```

(End definition for \keys_latex_options_package:n. This function is documented on page ??.)

`\keys_latex_options_local:` If local options are found, they are added to the processing list. L^AT_EX 2_ε stores options for each file in a macro which may or may not exist, hence the need to use `\cs_if_exist:c`.

```

72 \cs_new_protected_nopar:Npn \keys_latex_options_local:
73   {
74     \cs_if_eq:NNF \@currentt \@clsextension
75     {
76       \cs_if_exist:cT { opt@ \@currname . \@currentt }
77       {
78         \exp_args:NNc \clist_put_right:NV \keys_latex_options_clist
79           { opt@ \@currname . \@currentt }
80       }
81     }
82   }

```

(End definition for \keys_latex_options_local:. This function is documented on page ??.)

`\keys_latex_remove_equals:n` As the name suggests, this is a simple function to remove an equals sign from the input.
`\keys_latex_remove_equals:w` This is all wrapped up in an `n` function so that there will always be a sign available.

```

83 \cs_new:Npn \keys_latex_remove_equals:n #1
84   { \keys_latex_remove_equals:w #1 = \q_stop }
85 \cs_new:Npn \keys_latex_remove_equals:w #1 = #2 \q_stop {#1}

```

(End definition for \keys_latex_remove_equals:n. This function is documented on page ??.)

`\ProcessKeysOptions` The user macros are simply wrappers around the internal process. In contrast to other similar packages, the module name is always required here.

```

86 \cs_new_protected_nopar:Npn \ProcessKeysOptions #1
87   {
88     \bool_set_true:N \_l_keys_process_class_bool
89     \keys_latex_options:n {#1}
90   }
91 \cs_new_protected_nopar:Npn \ProcessKeysPackageOptions #1
92   {
93     \bool_set_false:N \_l_keys_process_class_bool

```

```

94   \keys_latex_options:n {#1}
95   }
96 \onlypreamble \ProcessKeysOptions
97 \onlypreamble \ProcessKeysPackageOptions
   (End definition for \ProcessKeysOptions. This function is documented on page 1.)
   One message to give.
98 \msg_new:nnnn { keyvalue } { option-unknown }
99   { Unknown-option-’#1’-for-package-#2. }
100  {
101    LaTeX-has-been-asked-to-set-an-option-called-’#1’-
102    but-the-#2-package-has-not-created-an-option-with-this-name.
103  }
104 </package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

	Symbols		
\@classoptionslist	38, 51, 53, 63	\clist_put_right:No	51
\@clsextension	40, 74	\clist_put_right:NV	78
\@current	40, 74, 76, 79	\clist_remove_all:Nn	68
\@currname	29, 76, 79	\cs_if_eq:NNF	38, 74
\@ifpackagelater	4	\cs_if_eq:NNTF	40
\@onlypreamble	96, 97	\cs_if_exist:cT	76
\@unprocessedoptions	34	\cs_new:Npn	83, 85
\@unusedoptionlist	57, 68	\cs_new_protected:Npn	17, 36, 48, 61
\@	10	\cs_new_protected_nopar:Npn	72, 86, 91
_l_keys_process_class_bool	16, 16, 43, 88, 93	\cs_set_eq:NN	34
			E
	A	\exp_args:NNc	78
\AtEndOfPackage	34	\ExplFileDate	3
	B	\ExplFileDescription	3
\bool_if:NT	43	\ExplFileName	3
\bool_new:N	16	\ExplFileVersion	3
\bool_set_false:N	93		K
\bool_set_true:N	88	\keys_define:nn	24
	C	\keys_if_exist:nnF	22
\clist_clear:N	19	\keys_if_exist:nnT	65
\clist_map_inline:Nn	53, 63	\keys_if_exist:nnTF	50, 55
\clist_new:N	15	\keys_latex_options:n	17, 17, 89, 94
\clist_put_right:Nn	56, 57, 67	\keys_latex_options_class:n	41, 48, 48
		\keys_latex_options_clist	15, 15, 19, 33, 51, 56, 67, 78

<code>\keys_latex_options_global:n</code>	20, 36 , 36		
<code>\keys_latex_options_local: ..</code>	21 , 72 , 72		
<code>\keys_latex_options_package:n</code>	44 , 61 , 61		
<code>\keys_latex_remove_equals:n</code>		
	55 , 65 , 83 , 83		
<code>\keys_latex_remove_equals:w</code>	. 83 , 84 , 85		
<code>\keys_set:nV</code>	33	
			P
			<code>\PackageError</code>
			7
			<code>\ProcessKeysOptions</code>
			1 , 86 , 86 , 96
			<code>\ProcessKeysPackageOptions</code>
			2 , 91 , 97
			<code>\ProvidesExplPackage</code>
			2
			Q
			<code>\q_stop</code>
			84 , 85
			S
			<code>\scan_stop:</code>
			34 , 38
			T
			<code>\tex_endinput:D</code>
			13
			L
<code>\l_keys_key_tl</code>	29	
			M
<code>\msg_error:nxxx</code>	28	
<code>\msg_new:nnnn</code>	98	