

The grffile package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2010/12/09 v1.13

Abstract

The package extends the file name processing of package `graphics` to support a larger range of file names. For example, the file name may contain several dots. Or in case of pdfTeX in PDF mode the file name may contain spaces.

Contents

1 Usage	2
1.1 Option <code>multidot</code>	2
1.2 Option <code>babel</code>	2
1.3 Option <code>extendedchars</code>	2
1.4 Option <code>encoding</code>	3
1.4.1 Option <code>inputencoding</code>	3
1.4.2 Option <code>filenameencoding</code>	3
1.4.3 Example	3
1.5 Option <code>space</code>	3
1.6 General use	4
1.7 Default settings	4
2 Implementation	4
2.1 Identification	4
2.2 Catcode stuff	4
2.3 Options	5
2.4 Fix <code>\Gin@ii</code> of package <code>graphicx</code>	11
3 Test	12
3.1 Multidot with default rule	12
4 Installation	13
4.1 Download	13
4.2 Bundle installation	13
4.3 Package installation	14
4.4 Refresh file name databases	14
4.5 Some details for the interested	14
5 References	15
6 History	15
[2004/07/18 v0.5]	15
[2006/08/15 v1.0]	15
[2006/08/17 v1.1]	15
[2006/11/30 v1.2]	15
[2007/04/11 v1.3]	15
[2007/06/13 v1.4]	15

[2007/08/16 v1.5]	15
[2007/11/11 v1.6]	15
[2007/11/24 v1.7]	15
[2008/08/11 v1.8]	15
[2008/10/13 v1.9]	16
[2009/09/25 v1.10]	16
[2010/01/28 v1.11]	16
[2010/08/26 v1.12]	16
[2010/12/09 v1.13]	16

7 Index	16
---------	----

1 Usage

1.1 Option **multidot**

The file name parsing of package `graphics` is changed, in order to detect known extensions. This allows both the use of dots inside the base file name and extensions with several dots.

Assume there are two files in the current directory: `Hello.World.eps` and `Hello.World.pdf`. `\includegraphics{Hello.World}` will find `Hello.World.pdf` with driver `pdftex` or `Hello.World.eps` with driver `dvips`.

Limitations: Problem could occur on systems, which don't use the dot as extension delimiter. These systems needs an own `texsys.cfg` containing definitions for `\filename@parse`. The author could not test that, due to a missing example.

1.2 Option **babel**

This option allows the use of shorthand characters of package `babel` inside the graphics file name. Additionally the tilde ‘~’ is supported. The option is turned on as default. (In version v1.1 or below of this package, the features of this option were part of option `extendedchars`.)

Example:

```
\usepackage[frenchb]{babel}
\usepackage{grffile}
Image: \includegraphics{C:/path/image}
```

1.3 Option **extendedchars**

If the input encoding is the same encoding as the encoding that is used for file names and the driver allows non-ascii characters. Without option `extendedchars` the 8-bit characters are expanded, if they are active characters. For example, see the L^AT_EX package `inputenc`. However a file name is not input for L^AT_EX. Therefore this option `extendedchars` removes the active status and the 8-bit characters are not expandable any more.

Example:

```
\usepackage[latin1]{inputenc}
\usepackage[extendedchars]{grffile}
\includegraphics{Bäckerstraße}
```

If the `draft` option of the `graphics` package is enabled, the file name is printed with the current font encoding for `\ttfamily`. Thus it is possible, that such characters are omitted or the wrong characters are displayed, if the font encoding is not the same as the file name encoding.

1.4 Option encoding

Consider the following scenario. Your file system is using UTF-8 as encoding for file names. But you use `latin1` as input encoding for your `TEX` files, because some packages are not ready for multi-byte encodings (`listings`, ...).

Then this option `encoding` loads support for converting encodings by loading package `stringenc`. The option is not defined after the preamble, because L^AT_EX limits package loading to the preamble.

File names are converted, if package `stringenc` is loaded and the encodings are known, see options `inputencoding` and `filenameencoding`.

1.4.1 Option `inputencoding`

Option `inputencoding` specifies the encoding of the file name in your `TEX` input file.

Package `inputenx` and package `inputenc` since version 2006/02/22 v1.1a remember the name of the input encoding that is looked up by this package. Therefore option `inputencoding` is usually not mandatory.

1.4.2 Option `filenameencoding`

This is the encoding of the filename of your file system. This option is mandatory, file names are not converted without this option. The option is disabled, if the value is empty.

1.4.3 Example

Back to the scenario where the file system uses UTF-8 and the L^AT_EX input files are encoded in `latin1`.

```
\usepackage[latin1]{inputenc}[2006/02/22]
% \usepackage[latin1]{inputenx}
\usepackage{graphicx}
\usepackage[encoding,filenameencoding=utf8]{grffile}
```

For older versions of package `inputenc` option `inputencoding` provides the necessary informations.

```
\usepackage[latin1]{inputenc}
\usepackage{graphicx}
\usepackage{grffile}
\grffilessetup{
    encoding,
    inputencoding=latin1,
    filenameencoding=utf8,
}
```

1.5 Option space

This option allows graphics file names that contain spaces if possible.

In general it is not possible to use space inside file names, because `TEX` considers the space character as termination in its syntax for commands that expect a file name.

Regarding graphics inclusion with the package `graphics` file names are used in two or three contexts:

1. The basic `\special` statement or primitive command for graphics inclusion. The `\special` statements for drivers `dvijs` or `dvipdfm` do not allow spaces. However pdf`TEX`'s primitive `\pdfximage` uses curly braces to delimit the file name and allows spaces. In case of X`TEX` file names can be enclosed in quotes to support spaces (at the cost that quotes no longer work).

2. `\includegraphics` checks the existence of the file. Also it looks for the right extension if the extension is not given.
- If pdfTeX 1.30 is given, the file existence test can be rewritten using a new primitive that allows spaces. This works in both modes DVI and PDF.
- In case of XeTeX the file existence test is rewritten to automatically add quotes.
- Sometimes files are read as TeX input files. For example, `.bb` files or MPS files.

If pdftex 1.30 or greater is used in PDF mode then the graphics file names may contain spaces except for MPS files. Therefore option `space` is only enabled by default, if the supported pdftex in PDF mode is detected or XeTeX is running. You can enable the option manually, if you know, your DVI driver supports spaces in its `\special` syntax and if there is no need to read the image file as TeX input file (third context).

1.6 General use

The options can be given at many places:

1. As package options:
`\usepackage[<options>]{grffile}`
2. Setup command of package `grffile`:
`\grffilessetup{<options>}`
3. The options are also available as options for package `graphicx`:
`\setkeys{Gin}{<options>}`
4. If package `graphicx` is loaded the options can also be applied for a single image:
`\includegraphics[<options>]{...}`

1.7 Default settings

<code>multidot</code>	<code>true</code>
<code>babel</code>	<code>true</code>
<code>extendedchars</code>	<code>false</code>
<code>space</code>	<code>true</code> if pdftex 1.30 or greater is used in PDF mode <code>false</code> otherwise

2 Implementation

2.1 Identification

```

1 {*package}
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{grffile}%
4 [2010/12/09 v1.13 Extended file name support for graphics (HO)]%
```

2.2 Catcode stuff

```

5 \edef\grffile@RestoreCatcodes{%
6   \catcode`\noexpand=\the\catcode`\=\relax
7   \catcode`\noexpand\:\the\catcode`\:\relax
8   \catcode`\noexpand\.\the\catcode`\.\relax
9   \catcode`\noexpand\'\the\catcode`\'\relax
10  \catcode`\noexpand\<\the\catcode`\<\relax
11  \catcode`\noexpand\>\the\catcode`\>\relax
12  \catcode`\noexpand*\the\catcode`\*\relax
```

```

13  \catcode`\noexpand\^{\the\catcode`\\relax
14  \catcode`\noexpand\~{\the\catcode`\\relax
15 }
16 \makeother\
17 \makeother:
18 \makeother`.
19 \makeother`
20 \makeother<
21 \makeother>
22 \makeother*
23 \catcode`\~=7 %
24 \catcode`\~=active

```

2.3 Options

```

25 \RequirePackage{ifpdf}[2010/01/28]
26 \RequirePackage{ifxetex}[2010/09/12]
27 \RequirePackage{kvoptions}[2006/08/17]
28 \SetupKeyvalOptions{%
29   family=Gin,%
30   prefix=grffile@%
31 }
32 \DeclareDefaultOption{@unknownoptionerror}
33 \DeclareBoolOption[true]{multidot}
34 \DeclareBoolOption[true]{babel}
35 \DeclareBoolOption>false{extendedchars}
36 \DeclareBoolOption{space}
37 \DeclareVoidOption{encoding}{%
38   \RequirePackage{stringenc}\relax
39 }
40 \DeclareStringOption{inputencoding}
41 \DeclareStringOption{filenameencoding}
42 \DeclareDefaultOption{%
43   \PassOptionsToPackage{CurrentOption{graphics}}%
44 }

```

Default setting for option space.

```

45 \RequirePackage{pdftexcmds}[2007/11/11]
46 \ifxetex
47   \grffile@spacetrue
48 \else
49   \begingroup\expandafter\expandafter\expandafter\endgroup
50   \expandafter\ifx\csname pdf@filesize\endcsname\relax
51     \grffile@spacefalse
52     \let\grffile@space@disabled\empty
53     \def\grffile@spacetrue{%
54       \PackageWarning{\grffile}{%
55         Option `space' is not available,\MessageBreak
56         because it needs pdfTeX >= 1.30 or XeTeX%
57       }%
58     }%
59   \else
60     \ifpdf
61       \grffile@spacetrue
62     \else
63       \grffile@spacefalse
64     \fi
65   \fi
66 \fi
67 \ProcessKeyvalOptions*
68 \AtBeginDocument{%
69   \DisableKeyvalOption[package=grffile]{Gin}{encoding}%
70 }

```

```

71 \RequirePackage{graphics}

\grffilesetup
72 \newcommand*\grffilesetup{%
73   \setkeys{Gin}%
74 }

grffile@org@Ginclude@graphics
75 \let\grffile@org@Ginclude@graphics\Ginclude@graphics

\Ginclude@graphics
76 \renewcommand*\Ginclude@graphics{%
77   \ifx\grffile@filenameencoding\empty
78   \else
79     \ifx\grffile@inputencoding\empty
80       \expandafter\ifx\csname inputencodingname\endcsname\relax
81         \expandafter\ifx\csname
82           CurrentInputEncodingOption\endcsname\relax
83         \else
84           \let\grffile@inputencoding\CurrentInputEncodingOption
85         \fi
86       \else
87         \let\grffile@inputencoding\inputencodingname
88       \fi
89     \fi
90     \ifx\grffile@inputencoding\empty
91     \else
92       \grffile@extendedcharstrue
93     \fi
94   \fi
95 \ifnum0\ifgrffile@babel 1\fi\ifgrffile@extendedchars 1\fi>\z@
96   \begingroup

Support of babel's shorthand characters.

97   \ifgrffile@babel
98     \csname @safe@activestrue\endcsname

Support of active tilde.

99   \edef~{\string~}%

Support of characters controlled by package inputenc.

100  \fi
101  \ifgrffile@extendedchars
102    \grffile@inputenc@loop\^A\^H%
103    \grffile@inputenc@loop\^K\^K%
104    \grffile@inputenc@loop\^N\^_%
105    \grffile@inputenc@loop\^?\^ff%
106  \fi
107  \expandafter\grffile@extchar@Ginclude@graphics
108 \else
109   \expandafter\grffile@Ginclude@graphics
110 \fi
111 }

file@extchar@Ginclude@graphics

112 \def\grffile@extchar@Ginclude@graphics#1{%
113   \toks@\{#1\}%
114   \edef\grffile@filename{\the\toks@}%
115   \ifx\grffile@inputencoding\empty
116   \else
117     \ifx\grffile@filenameencoding\empty
118     \else
119       \ifx\grffile@inputencoding\grffile@filenameencoding

```

```

120      \else
121          \expandafter\ifx\csname StringEncodingConvert\endcsname\relax
122              \PackageError{grffile}{%
123                  Package 'stringenc' is not loaded,\MessageBreak
124                  omitting file name conversion%
125              }{\@ehc}
126      \else
127          \StringEncodingConvert\grffile@temp\grffile@filename
128              \grffile@inputencoding\grffile@filenameencoding
129          \StringEncodingSuccessFailure{%
130              \let\grffile@filename\grffile@temp
131          }{%
132              \PackageError{grffile}{%
133                  Filename conversion failed%
134              }{\@ehc
135          }%
136      \fi
137      \fi
138      \fi
139  \fi
140  \toks@\expandafter{\grffile@filename}%
141  \edef\x{\endgroup
142      \noexpand\grffile@Ginclude@graphics{\the\toks@}%
143 }%
144  \x
145 }

```

\grffile@inputenc@loop

```

146 \def\grffile@inputenc@loop#1#2{%
147   \count@='#1\relax
148   \loop
149     \begingroup
150       \uccode`~=\count@
151     \uppercase{%
152       \endgroup
153       \edef~{\string~}%
154     }%
155   \ifnum\count@<'#2\relax
156     \advance\count@\\one
157   \repeat
158 }

```

Support for option space

\grffile@space@getbase

```

159 \def\grffile@space@getbase#1{%
160   \edef\grffile@tempa{%
161     \def\noexpand\@tempa####1#1\noexpand\@nil{%
162       \def\noexpand\Gin@base{####1}%
163     }%
164   }%
165   \grffile@IfFileExists{\filename@area\filename@base#1}{%
166     \grffile@tempa
167     \expandafter\@tempa\grffile@file@found\@nil
168     \edef\Gin@ext{#1}%
169   }{%
170   }%
171 }

172 \begingroup\expandafter\expandafter\expandafter\endgroup
173 \expandafter\ifx\csname pdf@filesize\endcsname\relax
174   \ifxetex

```

```

\grffile@XeTeX@IfFileExists
175  \long\def\grffile@XeTeX@IfFileExists#1{%
176    \openin`\inputcheck"##1" %
177    \ifeof`\inputcheck
178      \closein`\inputcheck
179      \expandafter`@secondoftwo
180    \else
181      \closein`\inputcheck
182      \expandafter`@firstoftwo
183    \fi
184  }%

\grffile@IfFileExists
185  \long\def\grffile@IfFileExists#1{%
186    \grffile@XeTeX@IfFileExists{#1}{%
187      \edef\grffile@file@found{#1}%
188      `@firstoftwo
189    }{%
190      \let\reserved@a`@secondoftwo
191      \ifx\input@path\undefined
192      \else
193        \expandafter`@tfor\expandafter\reserved@b\expandafter
194          :\expandafter=\input@path\do{%
195            \grffile@XeTeX@IfFileExists{\reserved@b#1}{%
196              \edef\grffile@file@found{\reserved@b#1}%
197              \let\reserved@a`@firstoftwo
198              `@break@tfor
199            }{}%
200          }%
201        \fi
202        \reserved@a
203    }%
204  }%

\grffile@org@Gread@QTm Patch \Gread@QTm of xetex.def.
205  \def\grffile@org@Gread@QTm#1{%
206    \IfFileExists{\Gin@base.bb}{%
207      \Gread@eps{\Gin@base.bb}%
208    }{%
209      \G@measure@QTm{\Gin@base}{\Gin@ext}%
210    }%
211  }%
212  \ifx\Gread@QTm\grffile@org@Gread@QTm

\Gread@QTm
213  \def\Gread@QTm#1{%
214    \grffile@IfFileExists{\Gin@base.bb}{%
215      \Gread@eps{\Gin@base.bb}%
216    }{%
217      \G@measure@QTm{\Gin@base}{\Gin@ext}%
218    }%
219  }%
220  \PackageInfo{\grffile}{\string\Gread@QTm\space patched}%
221 \else
222  \begingroup\expandafter\expandafter\expandafter\endgroup
223  \expandafter\ifx\csname Gread@QTm\endcsname\relax
224    \PackageWarning{\grffile}{%
225      \string\Gread@QTm\space of xetex.def not found%
226    }%
227  \else

```

```

\grffile@org@Gread@QTm
228      \let\grffile@org@Gread@QTm\Gread@QTm

\Gread@QTm
229      \def\Gread@QTm#1{%
230          \let\grffile@saved@iffileexists\IfFileExists
231          \let\IfFileExists\grffile@iffileexists
232          \grffile@org@Gread@QTm{#1}%
233          \let\IfFileExists\grffile@saved@iffileexists
234      }%

235      \fi
236      \fi
237 \else
238     \begingroup
239     \let\on@line\@empty
240     \PackageInfo{\grffile}{%
241         \string\grffile@iffileexists\space without space support,%
242         \MessageBreak
243         because pdfTeX's \string\pdffilesize\space is not available%
244         \MessageBreak
245         or XeTeX is not running%
246     }%
247   \endgroup

\grffile@iffileexists
248 \long\def\grffile@iffileexists#1{%
249     \IfFileExists{#1}{%
250         \let\grffile@ife@next\@firstoftwo
251     }{%
252         \let\grffile@file@found\@filef@und
253         \let\grffile@ife@next\@secondoftwo
254     }%
255     \grffile@ife@next
256 }%

257 \fi
258 \else

\grffile@iffileexists
259 \long\def\grffile@iffileexists#1{%
260     \expandafter\expandafter\expandafter
261     \ifx\expandafter\expandafter\expandafter\\pdf@filesize{#1}\\%
262     \let\reserved@a\@secondoftwo
263     \ifx\input@path\@undefined
264     \else
265         \expandafter\@tfor\expandafter\reserved@b\expandafter
266             :\expandafter=\input@path\do{%
267             \expandafter\expandafter\expandafter
268             \ifx\expandafter\expandafter\expandafter
269                 \\pdf@filesize{\reserved@b#1}\\%
270             \else
271                 \edef\grffile@file@found{\reserved@b#1}%
272                 \let\reserved@a\@firstoftwo
273                 \break@tfor
274             \fi
275         }%
276     \fi
277     \expandafter\reserved@a
278 \else
279     \edef\grffile@file@found{#1}%
280     \expandafter\@firstoftwo

```

```

281      \fi
282  }%
283 \fi

\grffile@Ginclude@graphics
284 \def\grffile@Ginclude@graphics#1{%
285   \begingroup
286   \ifgrffile@space
287     \let\Gin@getbase\grffile@space@getbase
288   \fi
289   \ifgrffile@multidot
290     \let\filename@base\empty
291     \let\filename@simple\grffile@filename@simple
292   \fi
293   \grffile@org@Ginclude@graphics{#1}%
294   \endgroup
295 }%

\grffile@filename@simple
296 \def\grffile@filename@simple#1.#2\\{%
297   \ifx\#2\\%
298     \def\filename@base{#1}%
299     \let\filename@ext\relax
300   \else
301     \def\filename@base{}%
302     \grffile@analyze@ext{#1}.{#2}\\%
303   \fi
304 }

\grffile@analyze@ext
305 \def\grffile@analyze@ext#1.#2\\{%
306   \let\grffile@next\relax
307   \ifx\#2\\%
308     \edef\filename@base{\filename@base#1}%
309     \let\filename@ext\relax
310     \def\grffile@next{\grffile@try@extlist}%
311   \else
312     \edef\filename@base{\filename@base #1}%
313     \edef\filename@ext{\filename@dot#2\\}%
314     \expandafter\ifx\csname Gin@rule@\.\filename@ext\endcsname\relax
315       \edef\filename@base{\filename@base.}%
316       \def\grffile@next{\grffile@analyze@ext#2\\}%
317     \else
318       \grffile@IfExists{\filename@area\filename@base.\filename@ext}{%
319         % success
320       }{%
321         \edef\filename@base{\filename@base.\filename@ext}%
322         \let\filename@ext\relax
323         \def\grffile@next{\grffile@try@extlist}%
324       }%
325     \fi
326   \fi
327   \grffile@next
328 }

\grffile@try@extlist
329 \def\grffile@try@extlist{%
330   \for\grffile@temp:=\Gin@extensions\do{%
331     \grffile@IfExists{\filename@area\filename@base\grffile@temp}{%
332       \ifx\filename@ext\relax
333         \edef\filename@ext{\expandafter\gobble\grffile@temp\empty}%

```

```

334      \fi
335  }{ }%
336 }%
337 \ifx\filename@ext\relax
338   \expandafter\let\expandafter\filename@base\expandafter\@empty
339   \expandafter\grffile@use@last@ext\filename@base.\@%
340 \fi
341 }

\grffile@use@last@ext
342 \def\grffile@use@last@ext#1.#2\@{%
343   \ifx\@#2\@%
344     \edef\filename@base{\expandafter\filename@dot\filename@base\@}%
345     \def\filename@ext{\#1}%
346     \expandafter\@gobble
347   \else
348     \edef\filename@base{\filename@base#1.}%
349     \expandafter\@firstofone
350   \fi
351   {%
352     \grffile@use@last@ext#2\@%
353   }%
354 }

```

Print current option setting

```

\grffile@option@status
355 \def\grffile@option@status#1{%
356   \begingroup
357   \let\on@line\@empty
358   \PackageInfo{\grffile}{%
359     Option '#1' is %
360     \expandafter\ifx\csname ifgrffile@\#1\expandafter\endcsname
361       \csname iftrue\endcsname
362     set to 'true'%
363   \else
364     \expandafter\ifx\csname grffile@\#1@disabled\endcsname\@empty
365       not available%
366     \else
367       set to 'false'%
368     \fi
369   \fi
370 }%
371 \endgroup
372 }

373 \grffile@option@status{multidot}
374 \grffile@option@status{extendedchars}
375 \grffile@option@status{space}

```

2.4 Fix \Gin@ii of package **graphicx**

If the image file name contains the hash character macro \Gin@ii of package **graphicx** breaks.

```

\grffile@Gin@ii@graphicx
376 \def\grffile@Gin@ii@graphicx[#1]#2{%
377   \def\@tempa{}%
378   \def\@tempb{\#2}%
379   \ifx\@tempa\@tempb
380     \def\@tempa{\Gin@iii[#1]\% hash-ok
381     \expandafter\@tempa

```

```

382 \else
383   \begingroup
384     \tempswafalse
385     \toks@{\Gin@include@graphics{#2}}%
386     \setkeys{Gin}{#1}%
387     \Gin@esetsize
388     \the\toks@
389   \endgroup
390 \fi
391 }

\grffile@Gin@ii@fixed
392 \def\grffile@Gin@ii@fixed[#1]{%
393   \def\@tempa{[]}%
394   \begingroup
395     \toks@={#2}%
396     \edef\@tempb{\the\toks@}%
397   \expandafter\endgroup
398   \ifx\@tempa\@tempb
399     \def\@tempa{\Gin@iii[#1] []% hash-ok
400     \expandafter\@tempa
401   \else
402     \begingroup
403       \tempswafalse
404       \toks@{\Gin@include@graphics{#2}}%
405       \setkeys{Gin}{#1}%
406       \Gin@esetsize
407       \the\toks@
408     \endgroup
409   \fi
410 }

\grffile@Fix@Gin@ii
411 \def\grffile@Fix@Gin@ii{%
412   \let\Gin@ii\grffile@Gin@ii@fixed
413   \begingroup
414     \escapechar=92 %
415     \PackageInfo{grffile}{\string\Gin@ii\space of package `graphicx' fixed}%
416   \endgroup
417 }

418 \ifx\Gin@ii\grffile@Gin@ii@graphicx
419   \grffile@Fix@Gin@ii
420 \else
421   \AtBeginDocument{\grffile@Fix@Gin@ii}%
422 \fi
423 \grffile@RestoreCatcodes
424 
```

3 Test

3.1 Multidot with default rule

```

425 {*test1}
426 \NeedsTeXFormat{LaTeX2e}
427 \documentclass{article}
428 \usepackage{filecontents}
429 % file grffile-test.mp:
430 % beginfig(1);
431 %   draw fullcircle scaled 2cm withpen pencircle scaled 2mm;
432 % endfig;

```

```

433 % end
434 \begin{filecontents*}{grffile-test.1}
435 %%PS
436 %%BoundingBox: -32 -32 32 32
437 %%Creator: MetaPost
438 %%CreationDate: 2004.06.16:1257
439 %%Pages: 1
440 %%EndProlog
441 %%Page: 1 1
442 0 5.66928 dtransform truncate idtransform setlinewidth pop [] 0 setdash
443 1 setlinejoin 10 setmiterlimit
444 newpath 28.34645 0 moveto
445 28.34645 7.51828 25.35938 14.72774 20.04356 20.04356 curveto
446 14.72774 25.35938 7.51828 28.34645 0 28.34645 curveto
447 -7.51828 28.34645 -14.72774 25.35938 -20.04356 20.04356 curveto
448 -25.35938 14.72774 -28.34645 7.51828 -28.34645 0 curveto
449 -28.34645 -7.51828 -25.35938 -14.72774 -20.04356 -20.04356 curveto
450 -14.72774 -25.35938 -7.51828 -28.34645 0 -28.34645 curveto
451 7.51828 -28.34645 14.72774 -25.35938 20.04356 -20.04356 curveto
452 25.35938 -14.72774 28.34645 -7.51828 28.34645 0 curveto closepath stroke
453 showpage
454 %%EOF
455 \end{filecontents*}
456 \usepackage{graphicx}
457 \usepackage[multidot]{grffile}[2008/10/13]
458 \DeclareGraphicsRule{*}{mps}{}{} % for pdflatex
459 \begin{document}
460 \includegraphics{grffile-test.1}
461 \end{document}
462 
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/grffile.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/grffile.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds.tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex grffile.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>grffile.sty</code>	→ <code>tex/latex/oberdiek/grffile.sty</code>
<code>grffile.pdf</code>	→ <code>doc/latex/oberdiek/grffile.pdf</code>
<code>test/grffile-test1.tex</code>	→ <code>doc/latex/oberdiek/test/grffile-test1.tex</code>
<code>grffile.dtx</code>	→ <code>source/latex/oberdiek/grffile.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk grffile.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{grffile.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
makeindex -s gind.ist grffile.idx
pdflatex grffile.dtx
```

5 References

- [1] David Carlisle, Sebastian Rahtz: *The graphics package*; 2006/02/20 v1.0o;
CTAN:/macros/latex/required/graphics/graphics.dtx.
- [2] Sebastian Rahtz, Heiko Oberdiek: *The graphicx package*; 1999/02/16 v1.0f;
CTAN:/macros/latex/required/graphics/graphicx.dtx.

6 History

[2004/07/18 v0.5]

- First version, published in newsgroup `de.comp.text.tex`:
“Re: Dateinamenproblem”²

[2006/08/15 v1.0]

- File existence check by new primitives of pdfTeX 1.30.
- Implementation partly rewritten.
- New DTX framework.

[2006/08/17 v1.1]

- Adaptation to version 2.3 of package `kvoptions`.

[2006/11/30 v1.2]

- New option `babel`. Before this feature was part of option `extendedchars`.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/06/13 v1.4]

- Encoding support added with options `encoding`, `inputencoding`, and `filenameencoding`.

[2007/08/16 v1.5]

- Bug fix in encoding support.

[2007/11/11 v1.6]

- Use of package `pdftexcmds` for LuaTeX support.

[2007/11/24 v1.7]

- Bug fix of broken previous version.

[2008/08/11 v1.8]

- Code is not changed.
- URLs updated.

²Url: <http://groups.google.com/group/de.comp.text.tex/msg/b85984095d1a3c95>

[2008/10/13 v1.9]

- Fix for option ‘multidot’ with default rule.

[2009/09/25 v1.10]

- Rewrite of ‘multidot’ algorithm to fix a problem (‘multidot’ with `\graphicspath`).

[2010/01/28 v1.11]

- Undefined `\pdf@filesize` fixed.

[2010/08/26 v1.12]

- Macro `\Gin@ii` of package `graphicx` fixed for the case that the file name contains a hash.

[2010/12/09 v1.13]

- Option space also supports X_ET_EX.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\'</code>	9, 19
<code>*</code>	12, 22
<code>\.</code>	8, 18
<code>\:</code>	7, 17
<code>\<</code>	10, 20
<code>\=</code>	6, 16
<code>\></code>	11, 21
<code>\@break@tfor</code>	198, 273
<code>\@ehc</code>	125, 134
<code>\@empty</code>	52, 77, 79, 90, 115, 117, 239, 290, 333, 338, 357, 364
<code>\@filef@und</code>	252
<code>\@firstofone</code>	349
<code>\@firstoftwo</code>	182, 188, 197, 250, 272, 280
<code>\@for</code>	330
<code>\@gobble</code>	333, 346
<code>\@inputcheck</code>	176, 177, 178, 181
<code>\@makeother</code>	16, 17, 18, 19, 20, 21, 22
<code>\@ne</code>	156
<code>\@nil</code>	161, 167
<code>\@secondoftwo</code>	179, 190, 253, 262
<code>\@tempa</code>	161, 167, 377, 379, 380, 381, 393, 398, 399, 400
<code>\@tempb</code>	378, 379, 396, 398
<code>\@tempswafalse</code>	384, 403
<code>\@tfor</code>	193, 265
<code>\@undefined</code>	191, 263
<code>\@unknownoptionerror</code>	32
<code>\\"</code>	261, 269, 296, 297, 302, 305, 307, 313, 316, 339, 342, 343, 344, 352
<code>\^</code>	13, 23, 102, 103, 104, 105
<code>\~</code>	14, 24, 150
	A
<code>\active</code>	24
<code>\advance</code>	156
<code>\AtBeginDocument</code>	68, 421
	B
<code>\begin</code>	434, 459
	C
<code>\catcode</code>	6, 7, 8, 9, 10, 11, 12, 13, 14, 23, 24
<code>\closein</code>	178, 181
<code>\count@</code>	147, 150, 155, 156
<code>\csname</code>	50, 80, 81, 98, 121, 173, 223, 314, 360, 361, 364
<code>\CurrentInputEncodingOption</code>	84
<code>\CurrentOption</code>	43
	D
<code>\DeclareBoolOption</code>	33, 34, 35, 36
<code>\DeclareDefaultOption</code>	32, 42
<code>\DeclareGraphicsRule</code>	458
<code>\DeclareStringOption</code>	40, 41
<code>\DeclareVoidOption</code>	37
<code>\DisableKeyvalOption</code>	69
<code>\do</code>	194, 266, 330
<code>\documentclass</code>	427
	E
<code>\end</code>	455, 461

\endcsname 50, 80, 82,
 98, 121, 173, 223, 314, 360, 361, 364
 \escapechar 414

F

\filename@area 165, 318, 331
 \filename@base 165,
 290, 298, 301, 308, 312, 315,
 318, 321, 331, 338, 339, 344, 348
 \filename@dot 313, 344
 \filename@ext 299, 309, 313, 314,
 318, 321, 322, 332, 333, 337, 345
 \filename@simple 291

G

\G@measure@QTM 209, 217
 \Gin@base 162, 206, 207, 209, 214, 215, 217
 \Gin@esetsize 387, 406
 \Gin@ext 168, 209, 217
 \Gin@extensions 330
 \Gin@getbase 287
 \Gin@ii 412, 415, 418
 \Gin@iii 380, 399
 \Ginclude@graphics 75, 76, 385, 404
 \Gread@eps 207, 215
 \Gread@QTM 212, 213, 220, 225, 228, 229
 \grffile@analyze@ext 302, 305
 \grffile@extchar@Ginlude@graphics
 107, 112
 \grffile@extendedcharstrue 92
 \grffile@file@found
 167, 187, 196, 252, 271, 279
 \grffile@filename 114, 127, 130, 140
 \grffile@filename@simple 291, 296
 \grffile@filenameencoding 77, 119, 128
 \grffile@Fix@Gin@ii 411, 419, 421
 \grffile@Gin@ii@fixed 392, 412
 \grffile@Gin@ii@graphicx 376, 418
 \grffile@Ginlude@graphics
 109, 142, 284
 \grffile@IFE@next 250, 253, 255
 \grffile@IfFileExists 165, 185,
 214, 231, 241, 248, 259, 318, 331
 \grffile@inputenc@loop
 102, 103, 104, 105, 146
 \grffile@inputencoding
 79, 84, 87, 90, 115, 119, 128
 \grffile@next 306, 310, 316, 323, 327
 \grffile@option@status
 355, 373, 374, 375
 \grffile@org@Ginlude@graphics
 75, 293
 \grffile@org@Gread@QTM 205, 212, 228
 \grffile@org@Gread@QTM 232
 \grffile@RestoreCatcodes 5, 423
 \grffile@savd@IfFileExists 230, 233
 \grffile@space@disabled 52
 \grffile@space@getbase 159, 287
 \grffile@spacefalse 51, 63
 \grffile@spacettrue 47, 53, 61
 \grffile@temp 127, 130, 330, 331, 333
 \grffile@tempa 160, 166

\grffile@try@extlist 310, 323, 329
 \grffile@use@last@ext 339, 342
 \grffile@XeTeX@IfFileExists
 175, 186, 195
 \grffilesetup 72
 \grffile@filenameencoding 117

I

\ifeof 177
 \IfFileExists 206, 230, 231, 233, 249
 \ifgrffile@babel 95, 97
 \ifgrffile@extendedchars 95, 101
 \ifgrffile@multidot 289
 \ifgrffile@space 286
 \ifnum 95, 155
 \ifpdf 60
 \ifx 50,
 77, 79, 80, 81, 90, 115, 117, 119,
 121, 173, 191, 212, 223, 261,
 263, 268, 297, 307, 314, 332,
 337, 343, 360, 364, 379, 398, 418
 \ifxetex 46, 174
 \includegraphics 460
 \input@path 191, 194, 263, 266
 \inputencodingname 87

L

\loop 148

M

\MessageBreak 55, 123, 242, 244

N

\NeedsTeXFormat 2, 426
 \newcommand 72

O

\on@line 239, 357
 \openin 176

P

\PackageError 122, 132
 \PackageInfo 220, 240, 358, 415
 \PackageWarning 54, 224
 \PassOptionsToPackage 43
 \pdf@filesize 261, 269
 \pdffilesize 243
 \ProcessKeyvalOptions 67
 \ProvidesPackage 3

R

\renewcommand 76
 \repeat 157
 \RequirePackage 25, 26, 27, 38, 45, 71
 \reserved@a 190, 197, 202, 262, 272, 277
 \reserved@b 193, 195, 196, 265, 269, 271

S

\setkeys 73, 386, 405
 \SetupKeyvalOptions 28
 \space 220, 225, 241, 243, 415
 \StringEncodingConvert 127
 \StringEncodingSuccessFailure 129

T	\uppercase	151	
\the	6, 7, 8, 9, 10, 11,	\usepackage	428, 456, 457
	12, 13, 14, 114, 142, 388, 396, 407		
\toks@	113, 114, 140,	X	
	142, 385, 388, 395, 396, 404, 407	\x	141, 144
U		Z	
\uccode	150	\z@	95